


## **Turbomix**

The ultimate vertical blender designed for the frozen dessert and pastry laboratory



λ



**Convenience** Immersion blender stands alone for ultimate comfort and ease of use. Desired mixing time can be set, allowing Turbomix to finish production autonomously. Optional Steel bucket available.

**Performance** Variable Speed motor is comfortably controlled by hand controls. Blender can be moved vertically and in 360° circular

Safety Activated by 2-handed control sensor.

Hygiene Emulsification blades can be taken apart and cleaned completely.







\*request it from your dealer to always keep your machine hygienically perfect.

carpigiani.com/us









Weights	lbs		kgs.	
Net	143	.3	65	
Crated	16	5	75	
	cu.	ft. c	:u. m.	
Volume	1.3	5	0.41	
Dimensions	in	in. c		
Width	17.	3	44	
Depth	19.	7	50	
Height	29.9 -	44.9 76	6 - 114	
Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Poles (P) Wires (W)	
230/50-60/1	10A	10A	1P, 1W	

## **Specifications**

## **Electrical**

A dedicated electrical connection is required. Manufactured to be permanently connected. See the Electrical chart for the proper electrical requirements. Consult your local Carpigiani distributor for cord & receptacle specifications as local codes allow.

445

## Motor RPM

3.000 - 12.000

Rotor Speed approx 22 m/sec


Minimum Quantity per Cycle 0.79 gal (3 liters)

Maximum Quantity per Cycle 3.96 gal (15 liters)

All specifications mentioned must be considered approximate; Carpigiani reserves the right to modify, without notice, all parts deemed necessary. This unit may be manufactured in other electrical characteristics and may have additional regulatory agency approvals, please consult the local Carpigiani Distributor. Check name plate for exact electrical data. \* Room temperature 68°F (20°C).

Bidding Specs								
Electrical	Volt	Hz	Ph	Neutral	□ Yes □ No	Cooling	🗖 Air	Water
Options								





an Ali Group Company

