

SLICER

BEST RESULTS

The HOBART slicers are suitable for varied types of products (meat, ham, cheese, carpaccio or cold cuts like frozen fish). Their top mounted sharpener guarantees accurate slicing. The special shape of the plate is responsible for a perfect product positioning. With a cutting range up to 22 mm the slicers can fulfil many different kinds of requirements. The well sliding carriage roller makes manual working very comfortable. The outstanding automatic slicer SL350AUTO-G comes with a display, which allows to select the speed of the carriage and the blade, as well as the carriage run and the number of slices to cut.

EASY HANDLING – HYGIENIC

The smooth anodized one-piece aluminium body provides best hygiene. Surfaces are durable and have no holes or edges where bacteria could grow. The knife cover as well as the sharpener are removable for simple cleaning. With the special designed ergonomic handle manual operation is very easy. At the automatic slicers carriage and blade speed can be adjusted separately.

DESIGN – QUALITY

The blade is made of hardened steel and ensures precise, clean cutting of the products. Smooth feeding of the slicer is possible thanks to the ribbed gauge plate and a front mounted product pusher. Together they facilitate the optimal product position. The adjusting knobs provide a precise control for shaving, chipping and slicing.

SAFETY

An irremovable blade guard ring protects the knife during operation and cleaning. In the event of a power cut the slicer must be restarted before operation can continue. The carriage can only be removed when the slice thickness control dial and the gauge tray is set to "0" and when the carriage is positioned at the start of the run at the operator side. The automatic slicer carriages move back to start position after slicing. All these features guarantee maximum safety during use, cleaning and maintenance.



SL300



SL350



SL300/350AUTO (belt)



SL350AUTO (gear)

TECHNICAL DATA



MODEL	SL300 (belt)	SL350 (belt/gear)	SL300/350AUTO (belt)	SL350AUTO (gear)
CUTTING RANGE in mm	0 – 14	0 – 19	0 – 14	0 – 22
POWER SUPPLY	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1	230 / 50 / 1
DIMENSIONS (H x W x D) in mm	600 x 560 x 570	670 x 600 x 590	600 x 580 x 805	680 x 680 x 840
NET WEIGHT in kg	29	40 / 42	46	50
CARRIAGE MOVEMENT in mm	290	365	290	365