


strada s

designed for
and by baristas.



Available Configurations: AV | ABR

Available Number of Groups: 2 | 3

Over the course of two years La Marzocco worked with thirty of the world's finest coffee professionals to design an espresso machine. This group was known as the “Street Team”. The Strada, which means Street in Italian, was named in their honor.

The second generation of the Strada improves upon the features and modernizes the aesthetics of the original. A lower profile invites customer engagement in a café setting, while also providing the barista an open, expansive work area.

The Strada platform has been designed to encourage creativity and customization so that each machine can be unique. The Strada is available in 2 different configurations to meet the specific needs of baristas and cafes around the world.

Insulated Boilers

Reduce energy consumption while contributing to temperature stability.

Adjustable Drip Tray - AV only

Allows you to use the machine with tall, to-go cups.

Integrated Scales - ABR only

Precision scales built into the drip tray provide an improved level of consistency.

Independent Saturated Boilers

Separate saturated boilers for each group head allow baristas to optimize temperature for individual coffees, ensuring thermal stability.

Proportional Steam Valve

Lever-style activation for proportional solenoid steam valve.

Programmable Doses

Auto-volumetrics ensure repeatability and consistency in high-volume settings.

Dual PID (coffee and steam)

Allows you to precisely control each coffee boiler as well as the steam boiler independently.

Digital Display

Intuitive programming makes it easy to adjust machine parameters and to monitor extraction times.

Cup Warmer - Special Order

Maintain espresso and cappuccino cups evenly heated at a proper temperature.

Pro Touch Steam Wands

High performing steam wands that are cool to the touch.

Hot Water Economizer

Enables you to fine-tune the tap water temperature for tea.

USB

Making it possible to easily update the machine's firmware.

3-button Interface

Control the machine using a simple 3-button interface, which can also be used to program the machine's settings.

Eco Mode

Can be programmed to enter stand-by mode, improving energy efficiency.

Pro App Compatible

Electronic board that allows connectivity with the La Marzocco Pro App.

Specifications	2 groups	3 groups
Height (cm/in)	50 / 19,7	50 / 19,7
Width (cm/in)	83 / 32,7	103 / 40,6
Depth (cm/in)	69 / 27,2	69 / 27,2
Weight (kg/lbs)	77 / 169,4	94 / 206,4
Voltage	200V Single Phase	200V Single Phase
	220V Single / 3 Phase	220V Single / 3 Phase
	380V 3 Phase	380V 3 Phase
Wattage (min)	4330	5830
Wattage (max)	5666	7783
Coffee Boiler Capacity (liters)	2,6	3,9
Steam Boiler Capacity (liters)	8,2	11,8