



Macadams Bread Slicers



A2



B2-XL



KB



KD

FEATURES & BENEFITS

- Choice of colours.
- Automatic cutting agent.
- Body coated with mild steel epoxy.
- Large removable crumb tray.
- All parts in contact with bread are stainless steel.
- Fitted with safety guard.
- Knives are stainless steel & re-sharpened to cut on up & down strokes.



	STANDARD SLICERS		GRAVITY FEED SLICERS	
	A2	B2-XL	KB	KD
Supply Voltage	220V	220V	380V	380V
Power Rating	0.55kW	0.55kW	0.55kW 3 phase	0.75kW 3 phase
R.P.M approx.	1450 rpm	1450 rpm	1450 rpm	1450 rpm
Switch / Control	Semi-automatic	Semi-automatic	Automatic	Automatic
Conveyance	V-belt driven	V-belt driven	V-belt driven	V-belt driven
Loaves per hour	±250 loaves	±250 loaves	±500 loaves	±1000 loaves
Max. loaf size (mm)	430 (w) X 130 (h)	330 (w) X 130 (h)	320 (w) X 140 (h)	310 (w) X 140 (h)
Slice thickness	Standard: 13mm Optional: 8mm - 16mm	Standard: 13mm Optional: 8mm - 16mm	Standard: 13mm Optional: 8mm - 16mm	Standard: 13mm Optional: 8mm - 16mm
Blade type	B2 blade (252mm hole to hole measurement)		KD blade (300mm hole to hole measurement)	
Dimensions (mm)	670(w) x 540(d) x 1110(h)	570(w) x 540(d) x 1110(h)	480(w) x 480(d) x 1200(h)	830(w) x 480(d) x 1200(h)
Weight: (kg)	105 kg	95 kg	110 kg	160 kg
PRODUCT CODE	BSK-90004	BSK-90014	BSK-90034	BSK-90045



Contact Details

HEAD OFFICE, EXPORTS & CAPE TOWN BRANCH Tel : +27 (21) 907-1000 Fax : +27 (21) 907-1111

JOHANNESBURG BRANCH Tel : (011) 472-4100 Fax : 086 618 6462

DURBAN BRANCH Tel : (031) 569-6290 Fax : (031) 569-6296

EMAIL info@macadams.co.za

WEBSITE www.macadams.co.za