robot @ coupe°


MP 450 Ultra




D

Pan capacity

up to 100 litres





A SALES DESCRIPTION

Ideal for blending soups and puréeing fruit and vegetables. Special institutional catering model intended for intensive use

B TECHNICAL DESCRIPTION

MP 450 Ultra stick blender. 230V/50Hz/1ph. Power: 500 W. Speed: 9,500 rpm. 100% stainless-steel blades, bell and tube (total length: 450 mm). "Easy Plug" system featuring detachable power cord

C TECHNICAL CHARACTERISTICS	
Effective output	500 W
Electrical data	230V/50Hz/1ph 2.1 A – plug supplied
Speed	9,500 rpm
Recyclability	95%
Net weight	4.9 kg
Reference	34810

STANDARDS

EN 12100-1 & 2-2004, EN 60204-1-2006, EN 12853, EN 60529-2000 : IP55 & IP34



E CHARACTERISTICS AND BENEFITS

MOTOR UNIT

- Power 500 W
- Stainless-steel motor unit with air vents in the top section only to ensure watertightness
- Lug on motor housing serves as a rest and pivot on the pan rim for greater user comfort
- Speed 9,500 rpm
- Self-regulating speed system
- New patented "Easy Plug" system making it easier to replace the power cord during after-sales servicing
- Cord winding system for tidy storage and optimum lifespan

TUBE AND BELL

- 100% stainless-steel blades, bell and tube (total length: 450 mm).
- Foot with detachable bell and blades (patented system exclusive to Robot-Coupe)

Update: June 2014

Watertight bell design for optimum lifespan

STANDARD ATTACHMENTS

- Wall-mounted stick blender holder
- Tool for fixing and detaching the blades



MP 450 Ultra

F

OPTIONAL ATTACHMENTS

- 3 adjustable stainless-steel pan supports:
 - Ref. 27363 for pans with a diameter of 330 650 mm
 - Ref. 27364 for pans with a diameter of 500 1000 mm
 - Ref. 27365 for pans with a diameter of 850 1300 mm
- 1 universal pan support:
 - Ref. 27354 screws onto pan rim





