


CE Mark	Electrical data				Dimensions (in mm)				Weight (kg)	
	Speed (rpm)	Power (Watts)	Intensity (Amp.)	Voltage* (Amp.)	A	B	C	D	net	gross
R 2	1 500	550	3.5	230 V/50 Hz 1	350	280	200	165	10	12
R 3 - 1500	1 500	650	5.7	230 V/50 Hz 1	400	210	210	200	13	14
R 3 - 3000	3 000	650	4.8	230 V/50 Hz 1	400	210	210	200	13	14
R 4	1 500 and 3 000	900	2.7	400 V/50 Hz 3	440	226	226	235	15	17
R 4 - 1500	1 500	700	2.7	230 V/50 Hz 1	440	226	226	235	15	17
R 4 V.V.	300 to 3 000	1 000	10	400 V/50 Hz 1	460	226	226	235	15	17
R 5 Plus	1 500 and 3 000	1 200	3.5	400 V/50 Hz 3	490	350	280	265	24	26
R 5 V.V.	300 to 3 000	1 300	13	230 V/50 Hz 60 Hz / 1	490	350	280	265	25	27
R 6	1 500 and 3 000	1 300	3.4	400 V/50 Hz 3	520	350	280	265	25	27
R 6 V.V.	300 to 3 000	1 500	13	230 V/50 Hz 60 Hz/1	520	350	280	265	26	28



*Other voltages available.

MODELES	Bowl capacity	Speed rpm	Motor base	Supply	Number of covers	Maximun quantities processed (kg)			
						Coarse mincing	Emulsion	Kneading	Grinding
R 2	2.9 litres	1500	ABS	Single phase	10 - 20	0.75	1.0	0.5	0.3
R 3 - 1500	3.7 litres	1500	ABS	Single phase	10 - 30	1.0	1.5	1.0	0.5
R 3 - 3000	3.7 litres	3000	ABS	Single phase	10 - 30	1.0	1.5	1.0	0.5
R 4	4.5 litres	1500 and 3000	Metallic	Three phase	10 - 50	1.5	2.5	1.3	0.9
R 4 - 1500	4.5 litres	1500	Metallic	Single phase	10 - 50	1.5	2.5	1.3	0.9
R 4 V.V.	4.5 litres	300 to 3000	Metallic	Single phase	10 - 40	1.5	2.5	1.3	0.9
R 5 Plus	5.5 litres	1500 and 3000	Metallic	Three phase	20 - 80	2.0	3.0	2.0	1.0
R 5 V.V.	5.5 litres	300 to 3000	Metallic	Single phase	20 - 80	2.0	3.0	2.0	1.0
R 6	7 litres	1500 and 3000	Metallic	Three phase	20 - 100	2.0	3.5	2.0	1.0
R 6 V.V.	7 litres	300 to 3000	Metallic	Single phase	20 - 100	2.0	3.5	2.0	1.0



R 3 • R 4 • R 4 V.V.

NEW

Polycarbonate lid designed to allow the addition of liquid or ingredients during processing.

4.5-litre stainless-steel bowl with handle for the R 4 and R 4 V.V. models and 3.7-litre stainless-steel bowl with handle for the R 3 model.

The **R 4 V.V.** has a speed range of **300 to 3 000 rpm**.



A **smooth blade** is supplied as a standard attachment, with cap which can be removed for cleaning.



Optional extras :

- **Serrated blade** assembly for grinding and kneading tasks.
- **Fine-serrated blade** assembly recommended for chopping parsley.



The **R 3** has a single speed of either **1 500 or 3 000 rpm**, depending on the model.

The **R 4** has a single speed of 1 500 rpm, or 2 speeds of **1 500 and 3 000 rpm**.

The **R 4-1500 model** has a single speed of **1 500 rpm**.