

OVERNIGHT THAW TECHNICAL DATASHEET

S10T-SS OVERNIGHT THAW



S10T-SS

Dimensions (mm)	External	Internal
Width	865	482
Depth	801	560
Height	1960	1370
Door Opening		1524
Capacity		
Max load capacity (kg)		35

*Per Section

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Easy to clean dished base with radiused corners
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing doors
- Precision injected, high density 75mm polyurethane insulation
- Heavy duty, non-marking swivel castors with brakes
- Barrel locked doors
- Product does not exceed 3°C throughout the thawing process

S20T-SS OVERNIGHT THAW



S20T-SS

Dimensions (mm)	External	Internal
Width	1655	482*
Depth	801	560
Height	1960	1370
Door Opening		1524
Capacity		
Max load capacity (kg)		70

OPTIONS

- Stainless steel back



OVERNIGHT THAW TECHNICAL DATA

Overnight Thaw	S10T-SS	S20T-SS
Temperature (°C)	0/+4	0/+4
Power Supply	220V/240V 50Hz/1Ph	220V/240V 50Hz/1Ph
Fuse (Amps)	13	13
Defrost	Automatic off cycle	Automatic off cycle
Noise Level (dBA)	59	60

Fittings

Shelves (427 x 550mm)	7	14
-----------------------	---	----

Electrical Data - Standard Refrigerant

Refrigerant	R134a	R134a
Energy Consumption (kW / 24hrs)*	4.3	5.8
Start Up (Amps)	10.7	19.7
Running (Amps)	5	7
Heat Rejection (kW / 24hrs)**	565	1114

IMPORTANT NOTES:

*Energy consumption is tested to EN153 in 24hrs

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

